

<b>Technical data R series (R150.4)</b>	
<b>Parameter</b>	<b>Value</b>
Channel	4//2
Power supply	11.5V-16V
Max power supply cable diam.	16 mm
Max output Cable diam.	12 mm
RMS Power 12V - 8 Ohm	4 x 75W
RMS Power 12V - 4 Ohm	4 x 150W
RMS Power 12V - 2 Ohm	4 x 300W
RMS Power 12V - 1 Ohm	4 x 450W
RMS Power 12V - Bridged 4 Ohm	2 x 600W
RMS Power "Tri-mode"	4 x 150W + 2 x 300W
I Max Amp.	70A
Signal to noise Ratio	>290 dB unweight
THD %	< 0.03%
Frequency range (-1 dB)	14 Hz-40.000 Hz
Input sensitivity	0.240 V-4 V
Input impedance	20 K Ohm
LP 24 dB	40 Hz -220 Hz
LP on-off	yes
HP 12 dB	40 Hz - 220 Hz
HP on-off	yes
Phase control	0° - 180° continuos
Slew rate	> 10 V/micro sec
Damping factor	> 290 constant
Power Led	yes
Alert led	yes
Fuse inside led	yes
Switching mo-st	yes
Dim. in mm	150 x 444 x 53