

GORDON MIXER MIX 1204



MIX 1204

SPECIFICATIONS

MONO INPUTS

MICROPHONE INPUTS (IMP "INCISIBLE" PREAMP)
GAIN RANGE +10 TO +60 dB
MAX. INPUT LEVEL +12 dBu @ +10 dB GAIN
IMPEDANCE APPROX. 2.6 k Ω BALANCED
SIGNAL-TO-NOISE RATIO 110 dB / 112 dB A-WEIGHTED
DISTORSION (THD+N) 0.005% / 0.004% A-WEIGHTED

LINE INPUT

IMPEDANCE APPROX. 20 k Ω BALANCED
10 k Ω BALANCED
GAIN RANGE -10 TO +40 dB
MAX. INPUT LEVEL 30 dBu

FREQUENCY RESPONSE

MICROPHONE INPUT TO MAIN OUT <10Hz - 90kHz (+0 dB/-1dB)

EQ STEREO CHANNELS

LOW 80Hz/±15 dB
MID 2.5 kHz/±15 dB
HIGH 12 kHz/±15 dB

AUX SENDS

MAX OUTPUT LEVEL +22dBu

STEREO AUX RETURNS

IMPEDANCE APPROX. 20 k Ω BAL./10 k Ω UNBAL
MAX INPUT LEVEL +22dBu

MAIN OUTPUTS

IMPEDANCE APPROX. 240 Ω BAL./120 Ω UNBAL.
MAX OUTPUT LEVEL +28 dBu
CONTROL ROOM OUTPUTS
IMPEDANCE APPROX. 120 Ω
MAX OUTPUT LEVEL +22dBu

MAIN SYSTEM DATA (PHYSICAL/WEIGHT)

DIMENSIONS (H x W x D) APPROX. 97x247x328mm
WEIGHT(NET) APPROX. 3Kg

